

# 40 Below™

## Flashing Tape



40 Below™ Flashing Tape is a 0.2mm thick - hot melt adhesive - flashing tape to seal around windows, doors, and other joinery openings as a secondary defence against water penetration. Adhesion from -40°C.


- Passes nail seal ability to ASTM D3330 and is **suitable as a single layer application** over timber frame.
- Not suitable where screw sealability is required
- Has been **CodeMark Certified** by Certmark International
- For a risk score between 0-20 in accordance with NZBC Acceptable Solution E2/AS1
- Passed NZS3604 Building Wind Zones up to and including 'Extra High'

### 40 Below™ Flashing Tape- Advantages

- **Compatible** with all building wraps
- Incredible adhesion in all conditions
- Simple 4 step installation, save time reducing costs
- Extremely thin only **0.2mm**, allows for easier fitting of windows and doors
- Reliable and dependable weather tightness
- Works in temperatures from **-40°C up to 65°C**
- An *Optional* **Corner Guard** is easy to install and increases protection to framing



Corner Guard



### Scope of Use / Applications

#### Windows/Door/Timber & Steel Frame Flashings

Masons 40 Below Flashing Tape and Masons Corner Guard must be installed in accordance with the instructions outlined on page 16 of this catalogue.



**No Need to use Primer Spray**



**No Need to use Heat Guns**

**RIGID AIR BARRIERS** – 40 Below is **tested and approved** for sealing the joints on Rigid barriers. Tested and approved for use by: BGC Durabarrier and OS'BraceRAP.

**Note:** 150mm Wide tape is used for 100mm wide window or door framing. 200mm wide tape is used for 140mm-150mm wide reveals.

40 Below™ flashing tape	Roll Sizes	Bunnings Code
40 Below flashing tape 75mm	H 75mm x L 20m	00281783
40 Below flashing tape 100mm	H 100mm x L 20m	00281786
40 Below flashing tape 150mm	H 150mm x L 20m	00281789
40 Below flashing tape 230mm	H 230mm x L 20m	00318724
Hydro corner guards	50	00290608